

## 4-Stripe Control Panel

## **Technical Specifications**

Stripes	<ul> <li>4 x panel stripes independently configurable for switcher, M/E, PREVIZ, or NDI™ output router operation</li> <li>Dynamic LCD crosspoint label displays</li> <li>Support for bank, layer and key delegation</li> <li>Support for multi-engine control</li> </ul>
Crosspoints	72 x crosspoints per stripe (24 buttons with 3 delegate banks)
COMPs	Direct panel access to VMC1 Video Mix Engine COMP Bin presets
Macro	Macro mode and number pads supporting attachment and activation of user-configured macros
Media	2 x media player control keypad with player delegation and command buttons
MEM	Direct panel access to VMC1 Video Mix Engine switcher and M/E MEMs
T-Bars	4 x multi-mode T-Bars (1 per stripe) with dynamically variable illumination and support for BKGD video layer and key layer delegation  • Fade  • Transition  • Fade to Black  • LiveSet™ Zoom
Joysticks	2 x multi-mode joysticks (3-axis) supporting stripe, layer and key delegation  • Position/Scale  • Rotate  • Crop  • LiveSet virtual camera control  • PTZ camera control  • Media player shuttle
NIC	1 Gigabit NIC
Physical	VMC1 4S chassis with 25W PSU  • 42.2 x 21.26 x 6.13 in (107.2 x 54.0 x 15.6 cm)  • 49.75 lbs (22.57 kg)

Subject to change without notice.

For complete technical specifications, please visit the IP Series page at www.newtek.com. Multi-standard pricing and availability may vary. Please contact your local reseller for details.