



Blackmagicdes

\$345

Connections

Total Video Inputs 4

Total Outputs

Total Aux Outputs 2

Total Audio Inputs 2 x 3.5mm stereo mini jack.

Total Audio Outputs None, embedded audio only.

Timecode Connection

ATEM SDI is fast to set up and easy to use. It includes 4 standards converted SDI inputs, USB webcam, 2 SDI outputs, Fairlight audio mixer with EQ and dynamics, DVE for picture in picture, transition effects, green screen chroma key, 20 stills

media pool for titles and free ATEM Software Control.

SDI Video Inputs 4 x 3G-SDI, 10-bit HD switchable. 2 channel embedded audio.

Video Input Re-Sync On all 4 SDI inputs.

Frame Rate and Format Converters On all 4 SDI inputs. SDI Program Outputs


2

Ethernet

Ethernet supports 10/100/1000 BaseT software control, software updates and direct or network panel connection.

Computer Interface

1 x USB Type-C 2.0 for webcam out, software control, software updates and panel connection.



Standards

HD Video Input Standards

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60 1080i50, 1080i59.94, 1080i60

HD Video Output Standards

1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

Video Streaming Standards

1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

Ultra HD Video Standards None

Video Sampling

4:2:2 YUV

Color Precision 10-bit

Color Space Rec 709

Colorspace Conversion Hardware based real time.

Product Specifics

Upstream Keyers

1

Downstream Keyers

1

Advanced Chroma Keyers

1

Linear/Luma Keyers

2

Audio

Audio Mixer

6 input x 2 channel mixer. Selectable On/Off/Audio-Follow-Video per channel plus separate gain control per channel. Level and Peak metering. Plus new Fairlight audio enhancements: Compressor, Gate, Limiter, 6 bands of parametric EQ. Master gain control.

Analog Input Unbalanced stereo

Transition Keyer

Total Number of Layers

Pattern Generators

Color Generators

DVE only.

5

1

2

Analog Input Delay Up to 8 frames

Input Impedance 1.8k

DVE With Borders and Drop Shadow 1

Interface Minimum monitor resolution of 1366 x 768.

Max Input Level +6dBV

Mic Plug In Power Available on both 3.5mm mini jack connections.

Media Player

Media Players

1

Channels Fill and key for each Media Player. Media Pool Still Image Capacity 20 with fill and key.

Media Pool Still Image Format PNG, TGA, BMP, GIF, JPEG and TIFF.

Control

Control Panel

Built in control panel. Software control panel included. Supports optional hardware panel.

Control Panel Connection

Ethernet supports 10/100 BaseT. Allows direct connection between panel and chassis, or via network. Also used for updating the software. ATEM SDI supports direct USB-C connection.

Control Panel Compatibility

Includes ATEM Software Control Panel. Also compatible with ATEM 1 M/E Advanced Panel and ATEM 2 M/E Broadcast Panel.

Control Panel Included

ATEM Software Control Panel included free for Mac 11.0 Big Sur, Mac 12.0 Monterey or later and Windows 10 or 11.

Software

Software Updates

Using USB or Ethernet connection directly connected to Mac OS X or Windows computers. Includes ATEM Switcher Utility.

Configuration

Set via ATEM Software Control Panel, excluding ATEM chassis IP address which is set via the ATEM Switcher Utility connected via USB to chassis.

Operating Systems



Mac 11.0 Big Sur, Mac 12.0 Monterey or later.



Power Requirements

Power Supply 1 x External 12V power supply. Power Usage 18W

Physical Specifications



Environmental Specifications

Operating Temperature 5° C to 40° C (41° - 104° F) **Storage Temperature** -10° to 60° C (14° to 140° F) **Relative Humidity** 0% to 90% non-condensing

What's Included

ATEM SDI External 12V DC power supply with international socket adapters

Warranty

12 Months Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2022, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. Privacy Policy

Blackmagic Design Authorized Reseller