

Mini Converter Sync Generator



Includes 6 crystal stabilized video reference outputs for referencing all the video equipment in your studio in either high definition Tri-Sync or standard definition Blackburst television standards. Perfect for small studios and outside broadcasts!

\$195

Connections

Analog Video Outputs

6 x common Blackburst or Tri Level reference outputs.

SDI Rates

270Mb, 1.5G.

Multi Rate Support

Via mini switches

Updates and Configuration

USB



Standards

Analog Format Support

525i29.97 NTSC, 625i25 PAL, 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080PsF23.98, 1080PsF24, 1080i50, 1080i59.94, 1080i60

Software

Software Control

Mac™ and Windows™ software upgrade via USB.

Internal Software Upgrade

Via included updater application.

Operating Systems



Mac 10.15 Catalina, Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

Settings Control

Mini Switches or USB software.

Power Requirements

Power Supply

+12V universal power supply included with international socket adapters for all countries. Cable tie point.

Power Consumption

3.00 Watts

Operational Voltage Range

12V DC

Physical Specifications



Environmental Specifications

Operating temperature 0° to 40° C (32° to 104° F)

Storage temperature -20° to 45° C (-4° to 113° F) Relative Humidity
0% to 90% non-condensing

What's Included

Mini Converter Sync Generator 12V universal power supply with international socket adapters

Warranty

3 Year Limited Manufacturer's Warranty.

uties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You ca pt out at any time by changing cookie settings. Privacy Policy				
Blackmagic Design Autho	rized Reseller			

All items on this website are copyright Blackmagic Design Pty. Ltd. 2022, all rights reserved. All trademarks are property of their respective owners. MSRP includes