

- - - - - - - - - - - - - - -

Blackmagic Videohub 20x20 12G

Blackmagic Videohub 20x20 12G is an advanced zero latency video router that supports any combination of SD, HD and Ultra HD on the router at the same time. It has 20 12G-SDI inputs and 20 12G-SDI outputs plus reference connections in a one rack unit size. The front panel LCD lets you see video before routing and clearly displays routing labels and video standards. Routing can be performed by direct button selection and using the large spin knob control that has an electronic clutch. It also features SDI re-clocking, external Ethernet control and supports all SDI video standards up to 2160p60.

Connections

SDI Video Inputs 20 SDI Video Outputs 20

SDI Rates

DVB-ASI, 270Mb, 1.5G, 3G, 6G, 12G.

Video Input Re-Sync None

SDI Reclocking On all SDI outputs.

Reference Inputs

SDI In

Tri-Sync or Black Burst.

\$2,395

Reference Outputs Reference terminating loop output.

Ethernet Supports 10/100/1000 BASE-T.

Computer Interface USB-C

SDI Out

Blackmagic Videohub 20x20 12G Q የ Ŷ q ſ Control Panel LCD Spin Menu Buttons Display Knob Buttons AC Power REF In Input and Out Y ፍጋ 00000000000 000000000000 የ የ Q 2 የ የ Г

Ethernet USB

Standards

SD Video Standards

525i59.94 NTSC, 625i50 PAL

HD Video Standards

720p50, 720p59.94, 720p60 1080i50, 1080i59.94, 1080i60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p47.95, 1080p48, 1080p50, 1080p59.94, 1080p60 1080PsF23,98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30

2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI, 2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI, 2Kp59.94 DCI, 2Kp60 DCI 2KPsF23.98 DCI, 2KPsF24 DCI, 2KPsF25 DCI, 2KPsF29.97 DCI, 2KPsF30 DCI

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p47.95, 2160p48, 2160p50, 2160p59.94, 2160p60

4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI, 4Kp29.97 DCI, 4Kp30 DCI, 4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI, 4Kp59.94 DCI, 4Kp60 DCI

SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M level A and B SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-10, ITU-R BT.656 and ITU-R BT.601

SDI Audio Sampling

Television standard sample rate of 48kHz and 24-bit.

SDI Video Sampling

YUV 4:2:2 and RGB 4:4:4

SDI Color Precision

10, 12-bit RGB 4:4:4 in all HD and 2K modes, Ultra HD modes up to 2160p30 and 4K modes up to 4Kp30 DCI. 10-bit YUV 4:2:2 in all modes.

SDI Color Space

REC 601, REC 709, REC 2020

SDI Auto Switching

Automatically selects between 270Mb SD-SDI, 1.5G HD-SDI, 3G level A and level B HD-SDI, 6G HD-SDI, 12G-SDI and DVB-ASI on each input so that each input can be running a different television standard.

SDI Metadata Support

Video payload identification ancillary data as per SMPTE 352M.

Control

Built in Control Panel

24 buttons for local control of Videohub with 3 buttons and search dial for menu control. 2.2 inch color display.

External Control Panel

Includes Blackmagic Videohub software control panel for Mac and Windows. Supports Videohub Smart Control Pro and Videohub Master Control Pro hardware panels. Includes Blackmagic Videohub SDK and Ethernet Videohub Control Protocol.

Control Panel Connection Ethernet

Software

Software Control

Router control included free for Windows™ and Mac™.

Internal Software Upgrade

Via included updater application.

Operating Systems



Mac 12.0 Monterey, Mac 13.0 Ventura or later.

Display

Displays

Built in 2.2 inch LCD for video and menu settings.

Power Requirements

Power Supply 1 x Internal 100 - 240V AC 50/60Hz.

IEC power cable required.

Power Fail Protection Crosspoint connections preserved and restored instantly at power on.

Windows 10, 64-bit.

Windows 11.

Power Usage 27.5 W max.

Physical Installation

1 rack unit height.

Physical Specifications



Environmental Specifications

Operating Temperature

0° to 40° C (32° to 104° F)

Storage Temperature -20° to 60° C (-4° to 140° F) **Relative Humidity** 0% to 90% non-condensing

What's Included

Blackmagic Videohub 20x20 12G Welcome wallet with QR code for software download

Warranty

3 Year Limited Manufacturer's Warranty, and 12 Month Warranty on the front panel.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2023, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. Privacy Policy

Blackmagic Design Authorized Reseller