

Switchers

4 Input HD digital video switcher

SE-650

| | |
|------------------------------------|--|
| Video Standard | HD |
| Video Format | 1080i 50/59.94/60Hz 720p 50/59.94/60Hz |
| Video Processing | SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB: 4:4:4 |
| Input Routable / Crosspoint | All 4, repeatable |
| Video Input | 2x HD-SDI 2x HDMI |
| Mix HD & SD Source | ---- |
| Computer Graphic Interface | 2 via HDMI |
| Video Output | 2 x HDMI (1 is MV, 1 is Assignable) 1 x HD-SDI (Assignable) |
| Down-converted Output | ---- |
| Built-in Multi-view Monitoring Out | HDMI & SDI assignable |
| Analogue Audio Input | 1 x Stereo RCA (L/R) 2 x Mono Microphone |
| Analogue Audio Output | 1 x Stereo RCA (L/R) 1 x Stereo headphone (Mini Jack with volume control) |
| Digital Embedded Audio Support | Input 2 channels, Output 2 channels |
| Audio Delay Calibration | ---- |
| A+V Switching | Yes |
| Chromakey | 1 |
| Title Creator | ---- |
| USK | 2x Keyer support Chromakey/ Linear/ Luma Key |
| DSK | 1x DSK support Lumakey/ Linear key (Key / Fill) |
| Picture in Picture | 1 |
| Logo Insertion | 1 |
| Still Store | 500 |
| Effects | FTB, Cut, 32 Wipe with border |
| Transition Preview | Full transitions preview |
| Sync / Reference In/Out | Built-in Genlock (internal) |
| Tally Output | 1x D-sub 15pin, dual color |
| PC Remote Control | DVIP (Ethernet) |
| Camera Control | ---- |
| Built-in Audio Mixer | Yes, 4 channels |

| | |
|-----------------------|---|
| Storage | ---- |
| Recording File System | ---- |
| Recording File Format | ---- |
| Video Encode | ---- |
| Audio Encode | ---- |
| Streaming Protocol | ---- |
| Firmware Update | USB |
| Special Features | Free Virtual Set and Stinger transition included |
| Chassis | Unibody |
| Dimension (LxWxH) | 400 x 250 x 82 mm |
| Weight | 1.9 kg |
| Power | DC 12V, 29W |
| Operating Temp. Range | 0~40 °C |
| What's in the Box | 1 x SE-650 product 1 x AD Switch DC 12V with AC Cord |